Acknowledgments

There are many people who have been helpful with the successful execution of this field program. First, we wish to thank Saffet Tanrikulu (CARB, CCOS principal investigator) and Andrew Ranzieri (CARB, CCOS technical committee chairman) for their tremendous support and cooperation. The logistical support given by Chuck McDade (ENSR) has been invaluable. We would also express our gratitude to Jim Jordan and Jesse Leach (NOAA / ETL) for their efforts making the radar wind profiler operational. We would also like to thank our colleague Roger Carter for his help setting up communications software so that data could be routinely downloaded. Special thanks are extended to thank Joyce Silvester for her assistance with the logistics of securing leases and phone lines.

We would like to thank Chuck Kuhnle for allowing us to use his ranch in the Carrizo Plain for deploying the radar wind profiler, Doppler sodar, and meteorological tower. Thanks are extended to Jay Courtney (San Luis Obispo Air Pollution Control District) for his logistical support for the Piedras Blancas monitoring site. Dan Freeman (DRI) is acknowledged for his help in securing the McKittrick site. We would like to acknowledge Carl Goff and Barry Oost (Kings County) for their aid for securing the necessary permits to deploy a meteorological tower at the Kettleman City site. David Freeman (Assistant Superintendent of Schools) kindly provided access to the Granite Bay site. We would like to also thank Ron Babcock, Scott Hixon, and Gary Gascoigne (Dept. Health Services) for use of their facilities in Suisun City. Special thanks go to Bill Shook (Chief of Natural Resources) and Don Neubacher (Superintendent) for allowing us to deploy a meteorological tower at the Point Reyes National Seashore. We would like to thank Rita Cirulis (Shasta Lake APCD), Charles Dahlen, and Fred Wyckoff (Shasta Lake Fire Protection District) for their cooperation securing a monitoring site in Shasta Lake. Finally, we would like to thank Bob Dietz (Manager) and Don Groundwater (facilities engineer) of the Bella Vista Water District for providing access to a monitoring site.

Support provided by Field Research Division to the California Air Resources Board is authorized under the Intergovernmental Cooperation Act (31 USC section 6505) which authorizes Federal agencies to provide specialized or technical services to the States or political subdivisions on a reimbursable basis. This research program was supported by the California Air Resources Board under contract number 00-2CCOS.

References

- U. S. Environmental Protection Agency, 1995: Quality Assurance Handbook for Air Pollution Measurement Systems, Volume IV: Meteorological Measurements. EPA-600/R-94-038d, Office of Research and Development, Research Triangle Park, NC.
- U. S. Environmental Protection Agency, 2000: Meteorological Monitoring Guidance for Regulatory Modeling Applications. EPA-454/R-99-005, Office of Air Quality Planning and Standards, Research Triangle Park, NC.
- Weber, B. L., and D. B. Wuertz, 1991: Quality control algorithm for profiler measurements of winds and temperatures. NOAA Technical Memorandum ERL WPL-212, Boulder, CO, 32 pp.
- Weber, B. L., D. B. Wuertz, D. C. Welsh, and R. McPeek, 1993: Quality controls for profiler measurements of winds and RASS temperatures. *J. Atmos. Oceanic Technol.*, **10**, 452-464.
- Wilczak, J. M., M. L. Cancillo, and C. W. King, 1997: A wind profiler climatology of boundary layer structure above the boreal forest. *J. Geophys. Res.*, **102**, 29083-29100.
- Yamartino, R. J., 1984: A comparison of several "single-pass" estimators of the standard deviation of wind direction. *J. Climate Appl. Meteor.*, **23**, 1362-1366.

Appendix A: Manufacturers

Campbell Scientific, Inc. 815 West 1800 North Logan, UT 84321-1784 (435) 753-2342 - tel (435) 750-9540 - fax www.campbellsci.com

Climatronics Corporation 140 Wilbur Place Bohemia, NY 11716 (631) 567-7300 - tel (631) 567-7585 - fax www.climatronics.com

Radian International LLC 5600 Airport Boulevard Boulder, CO 80301-2340 (303) 443-2378 - tel (303) 443-1628 - fax www.radian.com

R. M. Young Company 2801 Aero Park Drive Traverse City, MI 49686 (231) 946-3980 - tel (231) 946-4772 - fax www.rmyoung.com

Universal Manufacturing Company 43900 Groesbeck Highway Clinton Township, MI 48036 (810) 463-2560 - tel (810) 463-2964 - fax

Vaisala, Inc. 100 Commerce Way Woburn, MA 01801-1068 (781) 933-4500 - tel (781) 933-8029 - fax www.vaisala.com

Appendix B: Data Logger Program for Meteorological Towers

The following is the Campbell Scientific CR10 data logger program and associated comments for sensor cables and channels.

```
;{CR10X}
;CARB/CCOS, Written by Shane A. Beard, 04 MAY 00
;Analog Inputs:
;SE input 1, YELLOW, temperature (C)
;SE input 2, BLUE, relative humidity (%)
;SE input 3, CLEAR, wind direction (deg)
;Analog Grounds:
;AG, PURPLE, temperature
;Pulse Inputs:
;P1, CLEAR, wind speed
;Excitation Outputs:
;Ex1, RED, wind direction
;Control Ports:
;Ports 1 through 4 as needed for station address
;Power Connections:
;+12vdc, RED, temperature
;+12vdc, RED, wind speed
;+5vdc, ORANGE, temperature
;G, BLACK, wind speed
;G, BLACK, wind direction
;G, BLACK, temperature
;G, CLEAR, temperature
;G, SHIELD, wind speed
;G, SHIELD, wind direction
;Station Address Information:
;STN#1 CAR Carrizo Plain
;STN#2 PBL Piedras Blancas
;STN#3 MKT McKittrick
;STN#4 KET Kettleman City
;STN#5 GRN Granite Bay
;STN#6 SUI Suisun City
;STN#7 REY Point Reyes
;STN#8 SHA Shasta Lake
;STN#9 BEL Bella Vista
;Data Output Table:
;Record #
;Station #
;Year (YYYY)
;Julian Day (DDD)
;Time (HHMM)
;2-m temperature (C)
;2-m relative humidity (%)
;10-m scalar average wind speed (m/s)
```

```
;10-m vector average wind speed (m/s)
;10-m vector average wind direction (deg)
;10-m standard deviation of wind direction (deg)
;battery voltage
*Table 1 Program
      01: 1
                  Execution Interval (seconds)
1:
      Volt (SE) (P1)
      1: 1
                  Reps
      2: 5
                  2500 mV Slow Range
      3: 1
                  SE Channel
      4: 1
                  Loc [ temp_in_C ]
      5: .1
                  Mult
      6:-40
                  Offset
2:
     Volt (SE) (P1)
      1: 1
                  Reps
      2: 5
                  2500 mV Slow Range
      3: 2
                  SE Channel
      4: 2
                  Loc [ RH pct ]
      5: .1
                  Mult
      6: .0
                  Offset
3:
     Pulse (P3)
      1: 1
                  Reps
      2: 1
                  Pulse Channel 1
      3: 3
                  High Frequency, 16 Bit, All Counts
      4: 3
                  Loc [ windspeed ]
      5: .04287
                  Mult
      6: .22
                  Offset
4:
      Excite-Delay (SE) (P4)
      1: 1
                  Reps
      2: 15
                  2500 mV Fast Range
      3: 3
                  SE Channel
      4: 1
                  Excite all reps w/Exchan 1
      5: 1
                  Delay (units 0.01 sec)
      6: 2500
                  mV Excitation
      7: 4
                  Loc [ dir_deg ]
      8: .142
                  Mult
      9: .0
                  Offset
5:
      Batt Voltage (P10)
      1: 5
                  Loc [ battvolt ]
6:
     Read Ports (P25)
                  Mask (0..255)
      1: 15
      2: 6
                  Loc [ stn_numbr ]
7:
      If time is (P92)
      1: 0
                  Minutes (Seconds --) into a
      2: 5
                  Interval (same units as above)
      3: 10
                  Set Output Flag High (Flag 0)
```

```
8:
      Sample (P70)
      1: 1
                  Reps
      2: 6
                  Loc [ stn_numbr ]
9:
      Real Time (P77)
      1: 1220
                  Year, Day, Hour/Minute (midnight = 2400)
10:
      Average (P71)
      1:2
                   Reps
      2:1
                  Loc [ temp_in_C ]
11:
      Wind Vector (P69)
      1: 1
                  Reps
      2: 0
                  Samples per Sub-Intervals
      3: 02
                  s, U, \theta1, \sigma(\theta1) Polar
      4: 3
                  Wind Speed/East Loc [ windspeed ]
      5: 4
                  Wind Direction/North Loc [ dir_deg ]
12:
      Sample (P70)
      1: 1
                  Reps
                  Loc [ battvolt ]
      2: 5
*Table 2 Program
      01: 0
                  Execution Interval (seconds)
*Table 3 Subroutines
```

End Program